

What is claimed is:

1 1. A logical equivalence verifying device for performing logical
2 equivalence verification of two prescribed circuits to display the results thereof,
3 said device comprising:

4 a first identifier recording section that performs structural matching in
5 which it is determined whether there are those portions in corresponding logic
6 cones of said two circuits which correspond in circuit structure to each other,
7 and records each result of said structural matching as an identifier for each
8 element;

9 a subcone extracting section that extracts a plurality of collections of
10 elements as subcones from each of said logic cones, each element collection
11 including elements which are connected with each other and have the same
12 identifier;

13 a verifying section that verifies logical equivalence between said two
14 circuits for each subcone extracted by said subcone extracting section; and

15 a display control section that displays a first group of subcones with
16 mismatched results of said logical equivalence verification and a second group
17 of subcones with matched results of said logical equivalence verification while
18 distinguishing between these first and second groups of subcones based on the
19 results of said logical equivalence verification.

1 2. A logical equivalence verifying device for performing logical
2 equivalence verification of two prescribed circuits to display the results thereof,
3 said device comprising:

4 a second identifier recording section that performs instance name
5 matching for each element in which it is determined whether instance names of
6 elements in corresponding logic cones of said two circuits match each other,
7 and records the results of said instance name matching as identifiers,
8 respectively;

9 a subcone extracting section that extracts a plurality of element
10 collections as subcones from each of said logic cones, each element collection

including elements which are connected with each other and have the same identifier;

a verifying section that verifies logical equivalence between said two circuits for each subcone extracted by said subcone extracting section; and

a display control section that displays a first group of subcones with mismatched results of said logical equivalence verification and a second group of subcones with matched results of said logical equivalence verification while distinguishing between these first and second groups of subcones based on the results of said logical equivalence verification.

3. A logical equivalence verifying device for performing logical equivalence verification of two prescribed circuits to display the results thereof, said device comprising:

a subcone extracting section that extracts subcones from corresponding logic cones of said two circuits by excluding prescribed portions of said logic cones by providing an external input to each of said prescribed portions to make their output to be at a constant value;

a verifying section that verifies logical equivalence between said two circuits for each subcone extracted by said subcone extracting section; and

a display control section that displays a first group of subcones with mismatched results of said logical equivalence verification and a second group of subcones with matched results of said logical equivalence verification while distinguishing between these first and second groups of subcones based on the results of said logical equivalence verification.

4. The logical equivalence verifying device according to claim 3, wherein when said logic cone is divided into a plurality of portions by said prescribed portions, said subcone extracting section extracts said plurality of portions as subcones.

5. A logical equivalence verifying device for performing logical equivalence verification of two prescribed circuits to display the results thereof,

3 said device comprising:

4 an internal verification point associating section that selects internal
5 verification points in corresponding logic cones of said two circuits, respectively,
6 to observe outputs of portions thereof, and associates said internal verification
7 points of one of said circuits with those of the other circuit;

8 a subcone extracting section that extracts subcones from said logic
9 cones by using said internal verification points;

10 a verifying section that verifies logical equivalence between said two
11 circuits for each subcone extracted by said subcone extracting section; and

12 a display control section that displays a first group of subcones with
13 mismatched results of said logical equivalence verification and a second group
14 of subcones with matched results of said logical equivalence verification while
15 distinguishing between these first and second groups of subcones based on the
16 results of said logical equivalence verification.

1 6. The logical equivalence verifying device according to claim 1, wherein
2 said display control section displays, based on the results of said logical
3 equivalence verification, only those subcones for which said logical equivalence
4 verification has resulted in mismatch.

1 7. A logical equivalence verifying device for analyzing causes of logical
2 mismatch when a plurality of mismatched logic cones are detected which are
3 logically mismatched logic cones as a result of logical equivalence verification
4 between two prescribed circuits, said device comprising:

5 a storage section that stores elements constituting said mismatched
6 logic cones;

7 an analyzing section that extracts, as analysis elements among said
8 mismatched logic cones, those elements which constitute logic cones that have
9 been selected as objects for analysis, further extracts, as pertinent logic cones,
10 said mismatched logic cones including said analysis elements for each of said
11 analysis elements, and calculates the number of said pertinent logic cones as a
12 pertinent number for each of said analysis elements; and

13 a display control section that displays said pertinent number for each of
14 said analysis elements.

1 8. The logical equivalence verifying device according to claim 7, wherein
2 said display control section displays only those of said analysis elements for
3 which said pertinent number is within a prescribed range.

1 9. The logical equivalence verifying device according to claim 7, wherein
2 said display control section further displays an identifier of each of said
3 pertinent logic cones for each of said analysis elements.

1 10. The logical equivalence verifying device according to claim 7, wherein
2 said display control section highlights those output points which are subject to
3 influences due to a correction of elements.

1 11. The logical equivalence verifying device according to claim 7, wherein
2 said display control section highlights those output points which are subject to
3 influences due to a constraint of an input for excluding a prescribed portion not
4 to be verified.

1 12. The logical equivalence verifying device according to claim 1, wherein
2 said two prescribed circuits comprise a pre-change one and a post-change one
3 of a circuit being designed when said circuit is changed.

1 13. A logical equivalence verifying method for performing logical
2 equivalence verification of two prescribed circuits to display the results thereof,
3 said method comprising:

4 a step for performing structural matching in which it is determined
5 whether there are those portions in corresponding logic cones of said two
6 circuits which correspond in circuit structure to each other, and recording the
7 results of said structural matching as an identifier for each element;

8 a step for extracting a plurality of element collections as subcones from

9 each of said logic cones, each element collection including elements which are
10 connected with each other and have the same identifier;

11 a step for performing logical equivalence verification between said two
12 circuits for each of said subcones; and

13 a step for displaying a first group of subcones with mismatched results
14 of said logical equivalence verification and a second group of subcones with
15 matched results of said logical equivalence verification while distinguishing
16 between these first and second groups of subcones based on the results of said
17 logical equivalence verification.

1 14. A logical equivalence verifying method for performing logical
2 equivalence verification of two prescribed circuits to display the results thereof,
3 said device comprising:

4 a step for performing instance name matching for each element in
5 which it is determined whether instance names of elements in corresponding
6 logic cones of said two circuits match each other, and recording the results of
7 said instance name matching as identifiers, respectively;

8 a step for extracting a plurality of element collections as subcones from
9 each of said logic cones, each element collection including elements which are
10 connected with each other and have the same identifier;

11 a step for performing logical equivalence verification between said two
12 circuits for each of said subcones; and

13 a step for displaying a first group of subcones with mismatched results
14 of said logical equivalence verification and a second group of subcones with
15 matched results of said logical equivalence verification while distinguishing
16 between these first and second groups of subcones based on the results of said
17 logical equivalence verification.

1 15. A logical equivalence verifying method for performing logical
2 equivalence verification of two prescribed circuits to display the results thereof,
3 said method comprising:

4 a step for extracting subcones from corresponding logic cones of said

5 two circuits by excluding prescribed portions of said logic cones by providing an
6 external input to each of said prescribed portions to make their output to be at a
7 constant value;

8 a step for performing logical equivalence verification between said two
9 circuits for each of said subcones; and

10 a step for displaying a first group of subcones with mismatched results
11 of said logical equivalence verification and a second group of subcones with
12 matched results of said logical equivalence verification while distinguishing
13 between these first and second groups of subcones based on the results of said
14 logical equivalence verification.

1 16. A logical equivalence verifying method for performing logical
2 equivalence verification of two prescribed circuits to display the results thereof,
3 said method comprising:

4 a step for selecting internal verification points in corresponding logic
5 cones of said two circuits, respectively, to observe outputs of portions thereof,
6 and associating said internal verification points of one of said circuits with those
7 of the other circuit;

8 a step for extracting subcones from said logic cones by using said
9 internal verification points;

10 a step for performing logical equivalence verification between said two
11 circuits for each of said subcones; and

12 a step for displaying a first group of subcones with mismatched results
13 of said logical equivalence verification and a second group of subcones with
14 matched results of said logical equivalence verification while distinguishing
15 between these first and second groups of subcones based on the results of said
16 logical equivalence verification.

1 17. A logical equivalence verifying method for analyzing causes of logical
2 mismatch when a plurality of mismatched logic cones are detected which are
3 logically mismatched logic cones as a result of logical equivalence verification
4 between two prescribed circuits, said method comprising:

5 a step for storing elements constituting said mismatched logic cones;
6 a step for extracting, as analysis elements among said mismatched
7 logic cones, those elements which constitute logic cones that have been
8 selected as objects for analysis, further extracting, as pertinent logic cones,
9 said mismatched logic cones including said analysis elements for each of said
10 analysis elements, and calculating the number of said pertinent logic cones as
11 a pertinent number for each of said analysis elements; and
12 a step for displaying said pertinent number for each of said analysis
13 elements.

1 18. A logical equivalence verifying program for making a computer execute
2 a logical equivalence verifying method which performs logical equivalence
3 verification of two prescribed circuits to display the results thereof, said program
4 adapted to make said computer execute the steps of:

5 performing structural matching in which it is determined whether there
6 are those portions in corresponding logic cones of said two circuits which
7 correspond in circuit structure to each other, and recording the results of said
8 structural matching as an identifier for each element;

9 extracting a plurality of element collections as subcones from each of
10 said logic cones, each element collection including elements which are
11 connected with each other and have the same identifier;

12 performing logical equivalence verification between said two circuits for
13 each of said subcones; and

14 displaying a first group of subcones with mismatched results of said
15 logical equivalence verification and a second group of subcones with matched
16 results of said logical equivalence verification while distinguishing between
17 these first and second groups of subcones based on the results of said logical
18 equivalence verification.

1 19. A logical equivalence verifying program for making a computer execute
2 a logical equivalence verifying method which performs logical equivalence
3 verification of two prescribed circuits to display the results thereof, said program

4 adapted to make said computer execute the steps of:

5 performing instance name matching for each element in which it is
6 determined whether instance names of elements in corresponding logic cones
7 of said two circuits match each other, and recording the results of said instance
8 name matching as identifiers, respectively;

9 extracting a plurality of element collections as subcones from each of
10 said logic cones, each element collection including elements which are
11 connected with each other and have the same identifier;

12 performing logical equivalence verification between said two circuits for
13 each of said subcones; and

14 displaying a first group of subcones with mismatched results of said
15 logical equivalence verification and a second group of subcones with matched
16 results of said logical equivalence verification while distinguishing between
17 these first and second groups of subcones based on the results of said logical
18 equivalence verification.

1 20. A logical equivalence verifying program for making a computer execute
2 a logical equivalence verifying method which performs logical equivalence
3 verification of two prescribed circuits to display the results thereof, said program
4 adapted to make said computer execute the steps of:

5 extracting subcones from corresponding logic cones of said two
6 circuits by excluding prescribed portions of said logic cones by providing an
7 external input to each of said prescribed portions to make their output to be at a
8 constant value;

9 performing logical equivalence verification between said two circuits for
10 each of said subcones; and

11 displaying a first group of subcones with mismatched results of said
12 logical equivalence verification and a second group of subcones with matched
13 results of said logical equivalence verification while distinguishing between
14 these first and second groups of subcones based on the results of said logical
15 equivalence verification.

1 21. A logical equivalence verifying program for making a computer execute
2 a logical equivalence verifying method which performs logical equivalence
3 verification of two prescribed circuits to display the results thereof, said program
4 adapted to make said computer execute the steps of:

5 selecting internal verification points in corresponding logic cones of
6 said two circuits, respectively, to observe outputs of portions thereof, and
7 associating said internal verification points of one of said circuits with those of
8 the other circuit;

9 extracting subcones from said logic cones by using said internal
10 verification points;

11 performing logical equivalence verification between said two circuits for
12 each of said subcones; and

13 displaying a first group of subcones with mismatched results of said
14 logical equivalence verification and a second group of subcones with matched
15 results of said logical equivalence verification while distinguishing between
16 these first and second groups of subcones based on the results of said logical
17 equivalence verification.

1 22. A logical equivalence verifying program for making a computer execute
2 a logical equivalence verifying method for analyzing causes of logical mismatch
3 when a plurality of mismatched logic cones are detected which are logically
4 mismatched logic cones as a result of logical equivalence verification between
5 two prescribed circuits, said program adapted to make said computer execute
6 the steps of:

7 storing elements constituting said mismatched logic cones;

8 extracting, as analysis elements among said mismatched logic cones,
9 those elements which constitute logic cones that have been selected as objects
10 for analysis, further extracting, as pertinent logic cones, said mismatched logic
11 cones including said analysis elements for each of said analysis elements, and
12 calculating the number of said pertinent logic cones as a pertinent number for
13 each of said analysis elements; and

14 displaying said pertinent number for each of said analysis elements.